

US PATENT & TRADEMARK OFFICE

PATENT APPLICATION FULL TEXT AND IMAGE DATABASE



(1 of 1)

United States Patent Application**20200207823****Kind Code****A1****Gallant; Stuart ; et al.****July 2, 2020**

PROCESS FOR PRODUCING, ISOLATING, AND PURIFYING MODIFIED RECOMBINANT PROTEINS

Abstract

The invention provides for methods and processes for producing, isolating, and purifying modified proteins. In particular, the invention provides for the production, isolation and purification of PEGylated recombinant methionyl human granulocyte colony stimulating factor used for therapeutic purposes.

Inventors: **Gallant; Stuart;** *(Redwood City, CA)* ; **Ogez; John;** *(Redwood City, CA)* ; **Olson; Charles;** *(Redwood City, CA)*

Applicant:

| | Name | City | State | Country | Type |
|-----------|----------------------------------|--------------|-------|---------|------|
| Assignee: | Coherus Biosciences, Inc. | Redwood City | CA | US | |
| | Redwood City | | | | |
| | CA | | | | |

Family ID: **69375995**

Appl. No.: **16/728523**

Filed: **December 27, 2019**

4. The method of claim 3, further comprising, after step (h), storing the PEGylated r-met-Hu-G-CSF product at 5. \pm .3.degree. C.
5. The method of claim 1, further comprising after step (e): (f) suspending inclusion bodies comprising r-met-Hu-G-CSF in a solubilization buffer; (g) oxidizing solubilized r-met-Hu-G-CSF to permit the r-met-Hu-G-CSF to fold and form disulfide bonds; (h) subjecting a product of step (g) to Dowex flow-through chromatography; (i) subjecting a product of step (h) to acid precipitation; (j) subjecting a product of step (i) to anion exchange chromatography; (k) subjecting a product of step (j) to cation exchange chromatography; (l) subjecting a product of step (k) to mixed mode chromatography; (m) concentrating a product of step (l); and (n) exchanging r-met-Hu-G-CSF in the product of step (m) into a buffer by ultrafiltration and diafiltration.
6. The method of 2, further comprising after step (i): (j) contacting a r-met-Hu-G-CSF with a PEGylation reagent under suitable reaction conditions to PEGylate the r-met-Hu-G-CSF; (k) subjecting a product of step (j) to cation exchange chromatography to remove the reaction by-products from PEGylated r-met-Hu-G-CSF; (l) concentrating a product of step (k); (m) exchanging the PEGylated r-met-Hu-G-CSF in a product of step (l) into a buffer by ultrafiltration and diafiltration; (n) adding a surfactant to a product of step (m); (o) adjusting the pH of a product of step (n) to a target value by adding HCl or NaOH; (p) diluting a product of step (o) with additional diafiltration buffer to achieve a target PEGylated r-met-Hu-G-CSF concentration of 10.0 mg/mL; and (q) subjecting the PEGylated r-met-Hu-G-CSF product of step (p) to 0.2-.mu.m filtration.
7. The method of claim 5, further comprising after step (n): (o) contacting a r-met-Hu-G-CSF with a PEGylation reagent under suitable reaction conditions to PEGylate the r-met-Hu-G-CSF; (p) subjecting a product of step (o) to cation exchange chromatography to remove the reaction by-products from PEGylated r-met-Hu-G-CSF; (q) concentrating a product of step (p); (r) exchanging the PEGylated r-met-Hu-G-CSF in a product of step (q) into a buffer by ultrafiltration and diafiltration; (s) adding a surfactant to a product of step (r); (t) adjusting the pH of a product of step (s) to a target value by adding HCl or NaOH; (u) diluting a product of step (t) with additional diafiltration buffer to achieve a target PEGylated r-met-Hu-G-CSF concentration of 10.0 mg/mL; and (v) subjecting the PEGylated r-met-Hu-G-CSF product of step (u) to 0.2-.mu.m filtration.
8. The method of claim 7, further comprising storing the PEGylated r-met-Hu-G-CSF product at 5. \pm .3.degree. C.

Description

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to U.S. Provisional Patent Application Ser. No. 62/786,142, filed Dec. 28, 2018, the entire contents of which are herein incorporated by reference.

RELATED APPLICATIONS AND INCORPORATION BY REFERENCE

[0002] All documents cited or referenced in herein cited documents, together with any manufacturer's instructions, descriptions, product specifications, and product sheets for any products mentioned herein or in any document incorporated by reference herein, are hereby incorporated herein by reference, and may be employed in the practice of the invention. More specifically, all referenced documents are incorporated by reference to the same extent as if each individual document was specifically and individually indicated to be incorporated by reference.

FIELD OF THE INVENTION

[0003] The present invention generally relates to the production, isolation, and purification of a modified recombinant protein, specifically a protein used as a diagnostic, therapeutic, or prophylactic agent.

BACKGROUND OF THE INVENTION

[0004] Proteins for therapeutic use are available in suitable forms and in adequate quantities largely as a result of the advances in recombinant DNA technologies. Examples of recombinant therapeutic proteins include but are not limited to erythropoietin (EPO), granulocyte colony-stimulating factor (G-CSF), alpha-galactosidase A, alpha-L-iduronidase (rhIDU; laronidase), N-acetylgalactosamine-4-sulfatase (rhASB; galsulfase), dornase alfa (a Dnase), tissue plasminogen activator (TPA), glucocerebrosidase, interferons (IF s), insulin-like growth factor 1 (IGF-1), and rasburicase (a urate oxidase analog).

[0005] The availability of recombinant proteins has fostered advances in protein formulation and chemical modification. Chemical modification can facilitate protein protection as attachment of a chemical moiety may effectively block a proteolytic enzyme from physical contact with the protein backbone itself, and thus prevent degradation. Additional advantages include, but are not limited, to increasing the stability and circulation time of the therapeutic protein and decreasing immunogenicity. Polyethylene glycol ("PEG") is a chemical moiety which has been used in the preparation of therapeutic proteins. One specific therapeutic protein which has been chemically modified with PEG is G-CSF. G-CSF induces the rapid proliferation and release of white blood cells (e.g., neutrophilic granulocytes) into the blood stream, and thereby provides a therapeutic effect in fighting infection.

[0006] Development of successful production, isolation, and purification strategies for such chemically-modified recombinant proteins is challenging because of the problems associated with the scale-up of bioprocesses. The production, isolation, and purification of therapeutic proteins from various source materials involves a number of steps and procedures. These therapeutic proteins may be obtained from plasma or tissue extracts, for example, or may be produced by cell cultures using eukaryotic or prokaryotic cells containing at least one recombinant plasmid encoding the desired protein. The engineered proteins are then either secreted into the surrounding media or into the perinuclear space, or made intracellularly, for e.g., present in inclusion bodies, and extracted from the cells. A number of technologies are utilized for purifying desired proteins from their source material.

[0007] Purification processes comprise procedures in which the protein of interest is separated from the source materials on the basis of solubility, ionic charge, molecular size, adsorption properties, and specific binding to other molecules. The procedures include but are not limited to gel filtration chromatography, ion-exchange chromatography, affinity chromatography, hydrophobic interaction chromatography, and mixed-mode chromatography. The disclosed methods address the challenging problem of scaling up the production, isolation, and purification of modified recombinant human G-CSF for therapeutic purposes by providing an upstream process (UP) and a downstream process (DSP) as further described herein.

[0008] Citation or identification of any document in this application is not an admission that such document is available as prior art to the present invention.

SUMMARY OF THE INVENTION

[0009] Provided herein are processes and methods for producing, isolating, and purifying PEGylated, recombinant methionyl human granulocyte colony-stimulating factor (r-met-Hu-G-CSF) for therapeutic purposes, preferably on a commercial scale.

[0010] Provided herein are methods for producing recombinant methionyl human granulocyte colony-stimulating factor (r-met-Hu-G-CSF) that include: (a) contacting cells comprising a nucleic acid encoding r-met-Hu-G-CSF with a culture medium to create a fermentation medium; (b) fermenting the cells under fed-batch conditions causing the cells to produce r-met-Hu-G-CSF; (c) harvesting the cells from the fermentation medium by centrifugation; (d) lysing the cells harvested from the fermentation medium to release inclusion bodies comprising r-met-Hu-G-CSF; and (e) storing the inclusion bodies. Some embodiments further include, after step (e): suspending inclusion bodies comprising r-met-Hu-G-CSF in a solubilization buffer; (g) oxidizing solubilized r-met-Hu-G-CSF to permit the r-met-Hu-G-CSF to fold and form disulfide bonds; (h) subjecting a product of step (g) to Dowex flow-through chromatography; (i) subjecting a product of step (h) to acid precipitation; (j) subjecting a product of step (i) to anion exchange chromatography; (k) subjecting a product of step (j) to cation exchange chromatography; (l) subjecting a product of step (k) to mixed mode chromatography; (m) concentrating a product of step (l); and (n) exchanging r-met-Hu-G-CSF in the product of step (m) into a buffer by ultrafiltration and diafiltration. Some embodiments of any of the methods described herein further include after step (n): (o) contacting a r-met-Hu-G-CSF with a PEGylation reagent under suitable reaction conditions to PEGylate the r-met-Hu-G-CSF; (p) subjecting a product of step (o) to cation exchange chromatography to remove the reaction by-products from PEGylated r-met-Hu-G-CSF; (q) concentrating a product of step (p); (r) exchanging the PEGylated r-met-Hu-G-CSF in a product of step (q) into a buffer by ultrafiltration and diafiltration; (s) adding a surfactant to a product of step (r); (t) adjusting the pH of a product of step (s) to a target value by adding HCl or NaOH; (u) diluting a product of step (t) with additional diafiltration buffer to achieve a target PEGylated r-met-Hu-G-CSF concentration of 10.0 mg/mL; and (v) subjecting the PEGylated r-met-Hu-G-CSF product of step (u) to 0.2- μ m filtration. Some embodiments of any of the methods described herein further include storing the PEGylated r-met-Hu-G-CSF product at 5. \pm .3.degree. C.

[0011] Also provided herein are methods for purifying r-met-Hu-G-CSF from inclusion bodies that include: (a) suspending inclusion bodies comprising r-met-Hu-G-CSF in a solubilization buffer; (b) oxidizing solubilized r-met-Hu-G-CSF to permit the r-met-Hu-G-CSF to fold and form disulfide bonds; (c) subjecting a product of step (b) to Dowex flow-through chromatography; (d) subjecting a product of step (c) to acid precipitation; (e) subjecting a product of step (d) to anion exchange chromatography; (f) subjecting a product of step (e) to cation exchange chromatography; (g) subjecting a product of step (f) to mixed mode chromatography; (h) concentrating a product of step (g); and (i) exchanging r-met-Hu-G-CSF in the product of step (h) into a buffer by ultrafiltration and diafiltration. Some embodiments of any of the methods described herein further include after step (i): (j) contacting a r-met-Hu-G-CSF with a PEGylation reagent under suitable reaction conditions to PEGylate the r-met-Hu-G-CSF; (k) subjecting a product of step (j) to cation exchange chromatography to remove the reaction by-products from PEGylated r-met-Hu-G-CSF; (l) concentrating a product of step (k); (m) exchanging the PEGylated r-met-Hu-G-CSF in a product of step (l) into a buffer by ultrafiltration and diafiltration; (n) adding a surfactant to a product of step (m); (o) adjusting the pH of a product of step (n) to a target value by adding HCl or NaOH; (p) diluting a product of step (o) with additional diafiltration buffer to achieve a target PEGylated r-met-Hu-G-CSF concentration of 10.0 mg/mL; and (q) subjecting the PEGylated r-met-Hu-G-CSF product of step (p) to 0.2- μ m filtration.

[0012] Also provided herein are methods of producing a PEGylated and purified r-met-Hu-G-CSF that include: (a) contacting a r-met-Hu-G-CSF with a PEGylation reagent under suitable reaction conditions to PEGylate the r-met-Hu-G-CSF; (b) subjecting a product of step (a) to cation exchange chromatography to remove the reaction by-products from PEGylated r-met-Hu-G-CSF; (c) concentrating a product of step (b); (d) exchanging the PEGylated r-met-Hu-G-CSF in a product of step (c) into a buffer by ultrafiltration and diafiltration; (e) adding a surfactant to a product of step (d); (f) adjusting the pH of a product of step (e) to a target value by adding HCl or NaOH; (g) diluting a product of step (f) with additional diafiltration buffer to achieve a target PEGylated r-met-Hu-G-CSF concentration of 10.0 mg/mL; and (h) subjecting the PEGylated r-met-Hu-G-CSF product of step (g) to 0.2- μ m filtration. Some embodiments of any of the methods described herein further include, after step (h), storing the PEGylated r-met-Hu-G-CSF product at 5. \pm .3.degree. C.

[0013] Also provided herein is an upstream process (UP) which includes, but is not limited to, the following steps: Product Fermentation, Cell Harvest, Cell Lysis, and Inclusion Body Harvest and Wash. In some embodiments of any of the processes described herein, Product Fermentation is preceded by Primary Inoculum preparation.

[0014] Also provided herein is a downstream processes which includes, but is not limited to, the following steps: Inclusion Body Thaw/Solubilization/Oxidation, Dowex Chromatography, Acid Precipitation/Clarification, Anion Exchange Chromatography, Cation Exchange Chromatography, Mixed-mode Chromatography, UF/DF, PEGylation, and Bulk Formulation and Fill. In some embodiments of any of the processes described herein, the downstream process further includes a second Cation Exchange Chromatography step and a final UF/DF.

[0015] In particular embodiments of any of the processes or methods described herein, the upstream process begins with the inoculum stage using one or more vials of a cell bank. In some embodiments of any of the processes or methods described herein, the cell bank is a Master Cell bank (MCB) or a Working Cell Bank (WCB). In some embodiments, two vials of the cell bank are used. In some embodiments, two vials of a WCB are used. In some embodiments, the production-scale fermentation is performed using about a 1,000 L to about a 5,000 L (e.g., a 1,500-L) working volume fermenter. During the fermentation process, a continuous nutrient feed (fed-batch production) containing glucose, yeast extract, methionine, and leucine is added to maintain growth and minimize or prevent amino acid misincorporation. In some embodiments, the amino acid misincorporation is norvaline or norleucine incorporation. In some embodiments, product formation can be induced by addition of isopropyl-.beta.-D-thiogalactopyranoside (IPTG). The harvest operations separate the cells from the fermentation broth using, e.g., centrifugation. The cells are subsequently lysed by, e.g., high pressure homogenization to release the inclusion bodies (IB). The resuspended IB can then be washed by centrifugation. In some embodiments, the resulting washed inclusion bodies (WIB) can be, e.g., refrigerated before subsequent purification operations. In some embodiments, the resulting WIB can be frozen and stored for subsequent purification operations.

[0016] In some embodiments, the downstream process can begin by suspending the WIB slurry in a solubilization buffer. The target protein can be solubilized and then oxidized, allowing the peptide chain to fold and form disulfide bonds. The oxidized product can then be purified by Dowex flow-through chromatography, acid precipitation, anion exchange chromatography, cation exchange chromatography 1, and mixed mode chromatography. Following concentration and buffer-exchange by Ultrafiltration and Diafiltration 1 (UF/DF 1), the r-met-Hu-G-CSF can be PEGylated and the reaction by-products can be removed by the cation exchange chromatography 2 step. The purified PEGylated product can be concentrated and buffer-exchanged by a second UF/DF step (UF/DF 2). Polysorbate 20 can be added to the UF/DF 2 pool, and the pH of the formulation can be adjusted to a target value (e.g., any of the exemplary target values described herein). The product can be diluted with additional diafiltration buffer to achieve a target protein concentration of 10.0 mg/mL and 0.2-.mu.m filtered. The resulting PEGylated r-met-Hu-G-CSF is suitable as a drug substance and can be filled and stored in polyethylene terephthalate (PETG) bottles at 5.+-.3.degree. C.

[0017] It is noted that in this disclosure and particularly in the claims and/or paragraphs, terms such as "comprises," "comprised," "comprising" and the like can have the meaning attributed to it in U.S. patent law; e.g., they can mean "includes," "included," "including," and the like; and that terms such as "consisting essentially of" and "consists essentially of" have the meaning ascribed to them in U.S. patent law.

[0018] These and other embodiments are disclosed or are obvious from and encompassed by, the following Detailed Description.

DETAILED DESCRIPTION OF THE INVENTION

[0019] Provided herein are production, isolation, and purification processes or methods for PEGylated recombinant methionyl human granulocyte colony stimulating factor (r-met-Hu-G-CSF) which include an upstream process (UP) and/or a downstream processes (DSP), as described herein.

L, about 600 mL to about 800 mL, about 800 mL to about 5,000 L, about 800 mL to about 4,500 L, about 800 mL to about 4,000 L, about 800 mL to about 3,500 L, about 800 mL to about 3,000 L, about 800 mL to about 2,500 L, about 800 mL to about 2,000 L, about 800 mL to about 1,500 L, about 800 mL to about 1,000 L, about 1,000 mL to about 5,000 L, about 1,000 mL to about 4,500 L, about 1,000 mL to about 4,000 L, about 1,000 mL to about 3,500 L, about 1,000 mL to about 3,000 L, about 1,000 mL to about 2,500 L, about 1,000 mL to about 2,000 L, about 1,000 mL to about 1,500 L, about 1,500 mL to about 5,000 L, about 1,500 mL to about 4,500 L, about 1,500 mL to about 4,000 L, about 1,500 mL to about 3,500 L, about 1,500 mL to about 3,000 L, about 1,500 mL to about 2,500 L, about 1,500 mL to about 2,000 L, about 2,000 mL to about 5,000 L, about 2,000 mL to about 4,500 L, about 2,000 mL to about 4,000 L, about 2,000 mL to about 3,500 L, about 2,000 mL to about 3,000 L, about 2,000 mL to about 2,500 L, about 2,500 mL to about 5,000 L, about 2,500 mL to about 4,500 L, about 2,500 mL to about 4,000 L, about 2,500 mL to about 3,500 L, about 2,500 mL to about 3,000 L, about 3,000 mL to about 5,000 L, about 3,000 mL to about 4,500 L, about 3,000 mL to about 4,000 L, about 3,000 mL to about 3,500 L, about 3,500 mL to about 5,000 L, about 3,500 mL to about 4,500 L, about 3,500 mL to about 4,000 L, about 4,000 mL to about 5,000 L, about 4,000 mL to about 4,500 L, or about 4,500 mL to about 5,000 L).

[0030] In some embodiments, during the fermentation process, a continuous nutrient feed (fed-batch production) containing glucose, yeast extract, methionine, and leucine is added to maintain growth and minimize or prevent amino acid misincorporation. In some embodiments, the amino acid misincorporation is norleucine incorporation. In some embodiments, product formation is induced by addition of isopropyl- β -D-thiogalactopyranoside (IPTG). As used herein "IPTG" is a molecular mimic of allolactose, a lactose metabolite that triggers transcription of the lac operon, and it is therefore used to induce E. coli protein expression where the gene is under the control of the lac operator.

[0031] In some embodiments, the product fermentation process can occur in two stages. The first stage can consist of cell mass accumulation and rapid cell growth. The second stage can consist of the product induction phase, where IPTG is added to the culture and the temperature is lowered. In some embodiments, the amount of IPTG added to the culture is 14.1, 14.2, 14.3, 14.4, 14.5, 14.6, 14.7, 14.8, 14.9 or 15.0 L of a 100 mM IPTG solution, corresponding to a broth concentration of at least 1.0 mM IPTG based on initial bioreactor volume. Throughout the product fermentation stage, the bioreactor pH, temperature, dissolved oxygen (DO), pressure, and agitation are controlled within normal operating ranges.

Cell Harvest

[0032] The Cell Harvest step of the upstream process comprises harvest operations which separate the cells from the fermentation broth. In some embodiments, this step is conducted using centrifugation. High-level expression of many recombinant proteins in E. coli leads to the formation of highly aggregated protein commonly referred to as inclusion bodies (IBs). IBs are normally formed in the cytoplasm; however, if specific secretion vectors are used, they can form in the periplasmic space. IBs can be recovered from cell lysates by, e.g., low speed centrifugation.

[0033] Cell Lysis

[0034] The Cell Lysis step of the upstream process comprises processes whereby the cells are lysed to release IBs from the harvested cells. In some embodiments, cell lysis can be conducted using high pressure homogenization to release the IBs.

Inclusion Body Harvest and Wash

[0035] The Inclusion Body Harvest and Wash step of the upstream process comprises processes in which the resuspended IBs are washed and the resulting washed inclusion bodies (WIB) are frozen and stored for subsequent purification operations, thereby separating the IBs from the liquid phase of the cell lysate and removing cell debris.

[0036] In some embodiments, the IBs can be washed by centrifugation. In some embodiments, the feed flow rate is maintained at 4.0 L/min, 5.0 L/min, 6.0 L/min, 7.0 L/min, 8.0 L/min, 9.0 L/min, or 10.0 L/min, or about 4.0 L/min to about 10.0 L/min (e.g., about 4.0 L/min to about 9.0 L/min, about 4.0 L/min to about 8.0 L/min, about 4.0 L/min to about 7.0 L/min, about 4.0 L/min to about 6.0 L/min, about 4.0 L/min to about 5.0 L/min, about 5.0 L/min to about 10.0 L/min, about 5.0 L/min to about 9.0 L/min, about 5.0 L/min to about 8.0 L/min, about 5.0 L/min to about 7.0 L/min, about 5.0 L/min to about 6.0 L/min, about 6.0 L/min to about 10.0 L/min, about 6.0 L/min to about 9.0 L/min, about 6.0 L/min to about 8.0 L/min, about 6.0 L/min to about 7.0 L/min, about 7.0 L/min to about 10.0 L/min, about 7.0 L/min to about 9.0 L/min, about 7.0 L/min to about 8.0 L/min, about 8.0 L/min to about 10.0 L/min, about 8.0 L/min to about 9.0 L/min, or about 9.0 L/min to about 10.0 L/min) and the centrate/centrifuge back pressure can be maintained at 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, or 55 psig, or about 45 psig to about 55 psig (e.g., about 45 psig to about 54 psig, about 45 psig to about 52 psig, about 45 psig to about 50 psig, about 45 psig to about 48 psig, about 46 psig to about 55 psig, about 46 psig to about 54 psig, about 46 psig to about 52 psig, about 46 psig to about 50 psig, about 46 psig to about 48 psig, about 48 psig to about 55 psig, about 48 psig to about 54 psig, about 48 psig to about 52 psig, about 48 psig to about 50 psig, about 50 psig to about 55 psig, about 50 psig to about 54 psig, about 50 psig to about 52 psig, or about 52 psig to about 55 psig). In some embodiments, the resulting IB paste can be resuspended with purified water. In some embodiments, the resultant resuspended total pool mass can be in the range of about 1576 kg to about 1624 kg (e.g., about 1576 kg to about 1620 kg, about 1576 kg to about 1610 kg, about 1576 kg to about 1600 kg, about 1576 kg to about 1590 kg, about 1576 kg to about 1580 kg, about 1580 kg to about 1624 kg, about 1580 kg to about 1620 kg, about 1580 kg to about 1610 kg, about 1580 kg to about 1600 kg, about 1580 kg to about 1590 kg, about 1590 kg to about 1624 kg, about 1590 kg to about 1620 kg, about 1590 kg to about 1610 kg, about 1590 kg to about 1600 kg, about 1600 kg to about 1624 kg, about 1600 kg to about 1620 kg, about 1600 kg to about 1610 kg, about 1610 kg to about 1624 kg, about 1610 kg to about 1620 kg, or about 1620 kg to about 1624 kg). In some embodiments, the resultant total pool mass is about 1590 kg, about 1595 kg, about 1600 kg, about 1605 kg, about 1610 kg, about 1615 kg, or about 1620 kg.

Downstream Process

[0037] The downstream process (DSP) steps include, but are not limited to, the following: Inclusion Body Thaw/Solubilization/Oxidation, Purification (e.g., Dowex Chromatography, Acid Precipitation/Clarification, Anion Exchange Chromatography, Cation Exchange Chromatography, and Mixed-mode Chromatography), Buffer Exchange (e.g., Ultrafiltration and Diafiltration), and PEGylation. In some embodiments, the DSP can further include Bulk Formulation and Fill.

[0038] In one embodiment, the DSP steps can include, but are not limited to, the following: Inclusion Body Thaw/Solubilization/Oxidation, Purification (e.g., Dowex Chromatography, Acid Precipitation/Clarification, Anion Exchange Chromatography, Cation Exchange Chromatography, and Mixed-mode Chromatography), Buffer Exchange (e.g., UF/DF), PEGylation, Purification of the PEGylated product (e.g., a second Cation Exchange Chromatography), Buffer Exchange into product formulation buffer (e.g., UF/DF 2), and Formulation and Fill.

Thaw/Solubilization/Oxidation

[0039] The DSP can begin with the thaw of a specified mass of frozen WIB. The WIB Thaw/Solubilization/Oxidation step of the DSP functions to fold the product into its active conformation and form the appropriate disulfide bonds. In some embodiments, the mass of frozen WIB thawed is from a maximum of two upstream batches. The inclusion body slurry can be suspended in a solubilization buffer. The protein can be solubilized and then oxidized, allowing the peptide chain to fold and form disulfide bonds.

[0040] In some embodiments, the mass of thawed WIB containing the expressed r-met-Hu-G-CSF that is transferred into the solubilization solution is

about 1188 g, about 1190 g, about 1200 g, about 1210 g, or about 1212 g, or about 1180 g to about 1220 g (e.g., about 1180 g to about 1210 g, about 1180 g to about 1200 g, about 1180 g to about 1190 g, about 1190 g to about 1220 g, about 1190 g to about 1210 g, about 1190 g to about 1200 g, about 1200 g to about 1220 g, about 1200 g to about 1210 g, or about 1210 g to about 1220 g). In some embodiments, the final buffer composition of the solubilization solution comprises about 7 g/L, about 8 g/L, about 9 g/L, about 10 g/L, about 11 g/L, or about 12 g/L Sarkosyl. In some embodiments, the solubilization solution comprises about 7.0 g/L to about 12.0 g/L (e.g., about 7.0 g/L to about 11.5 g/L, about 7.0 g/L to about 11.0 g/L, about 7.0 g/L to about 10.5 g/L, about 7.0 g/L to about 10.0 g/L, about 7.0 g/L to about 9.5 g/L, about 7.0 g/L to about 9.0 g/L, about 7.0 g/L to about 8.5 g/L, about 7.0 g/L to about 8.0 g/L, about 7.0 g/L to about 7.5 g/L, about 7.5 g/L to about 12.0 g/L, about 7.5 g/L to about 11.5 g/L, about 7.5 g/L to about 11.0 g/L, about 7.5 g/L to about 10.5 g/L, about 7.5 g/L to about 10.0 g/L, about 7.5 g/L to about 9.5 g/L, about 7.5 g/L to about 9.0 g/L, about 7.5 g/L to about 8.5 g/L, about 7.5 g/L to about 8.0 g/L, about 8.0 g/L to about 12.0 g/L, about 8.0 g/L to about 11.5 g/L, about 8.0 g/L to about 11.0 g/L, about 8.0 g/L to about 10.5 g/L, about 8.0 g/L to about 10.0 g/L, about 8.0 g/L to about 9.5 g/L, about 8.0 g/L to about 9.0 g/L, about 8.0 g/L to about 8.5 g/L, about 8.5 g/L to about 12.0 g/L, about 8.5 g/L to about 11.5 g/L, about 8.5 g/L to about 11.0 g/L, about 8.5 g/L to about 10.5 g/L, about 8.5 g/L to about 10.0 g/L, about 8.5 g/L to about 9.5 g/L, about 8.5 g/L to about 9.0 g/L, about 9.0 g/L to about 12.0 g/L, about 9.0 g/L to about 11.0 g/L, about 9.0 g/L to about 10.5 g/L, about 9.0 g/L to about 10.0 g/L, about 9.0 g/L to about 9.5 g/L, about 9.5 g/L to about 12.0 g/L, about 9.5 g/L to about 11.5 g/L, about 9.5 g/L to about 11.0 g/L, about 9.5 g/L to about 10.5 g/L, about 9.5 g/L to about 10.0 g/L, about 10.0 g/L to about 12.0 g/L, about 10.0 g/L to about 11.5 g/L, about 10.0 g/L to about 11.0 g/L, about 10.0 g/L to about 10.5 g/L, about 10.5 g/L to about 12.0 g/L, about 10.5 g/L to about 11.5 g/L, about 10.5 g/L to about 11.0 g/L, about 11.0 g/L to about 12.0 g/L, about 11.0 g/L to about 11.5 g/L, or about 11.5 g/L to about 12.0 g/L) Sarkosyl. In some embodiments, the final buffer composition of the solubilization solution comprises about 10 mM, about 15 mM, about 20 mM, or about 25 mM Tris. In some embodiments, the solubilization solution comprises about 10 mM to about 25 mM (e.g., about 10 mM to about 20 mM, about 10 mM to about 15 mM, about 15 mM to about 25 mM, about 15 mM to about 20 mM, about 20 mM to about 25 mM) Tris. In some embodiments, the final buffer composition of the solubilization solution has a pH of about 7.8, about 7.9, about 8.0, about 8.1, or about 8.2, or about 7.8 to about 8.2 (e.g., about 7.8 to about 8.1, about 7.8 to about 8.0, about 7.9 to about 8.2, about 7.9 to about 8.1, or about 8.0 to about 8.2). In some embodiments, the product concentration in the solubilization pool is about 4 g/L, about 4.5 g/L, about 5.0 g/L, or about 5.5 g/L, or about 4.0 g/L to about 5.5 g/L (e.g., about 4.0 g/L to about 5.0 g/L, about 4.0 g/L to about 4.5 g/L, about 4.5 g/L to about 5.5 g/L, about 4.5 g/L to about 5.0 g/L, or about 5.0 g/L to about 5.5 g/L). In some embodiments, the solubilization time is about 1.5 hours, about 2.0 hours, or about 2.5 hours, or about 1.5 hours to about 2.5 hours (e.g., about 1.5 hours to about 2.0 hours, or about 2.0 hours to about 2.5 hours). During the oxidation phase, the refold process is controlled at pH of about 7.8, about 7.9, about 8.0, about 8.1, or about 8.2, or about 7.8 to about 8.2 (e.g., about 7.8 to about 8.1, about 7.8 to about 8.0, about 7.9 to about 8.2, about 7.9 to about 8.1, or about 8.0 to about 8.2). In some embodiments, the refold process is controlled at temperature of about 17.degree. C., about 18.degree. C., about 19.degree. C., about 20.degree. C., about 21.degree. C., about 22.degree. C., or about 23.degree. C., or about 17.degree. C. to about 23.degree. C. (e.g., about 17.degree. C. to about 22.degree. C., about 17.degree. C. to about 21.degree. C., about 17.degree. C. to about 20.degree. C., about 17.degree. C. to about 19.degree. C., about 18.degree. C. to about 23.degree. C., about 18.degree. C. to about 22.degree. C., about 18.degree. C. to about 21.degree. C., about 18.degree. C. to about 20.degree. C., about 19.degree. C. to about 23.degree. C., about 19.degree. C. to about 22.degree. C., about 19.degree. C. to about 21.degree. C., about 20.degree. C. to about 23.degree. C., about 20.degree. C. to about 22.degree. C., or about 21.degree. C. to about 23.degree. C.).

Purification

[0041] In some embodiments, G-CSF can be purified by one or more of: flow-through chromatography, Acid Precipitation/Clarification, Anion Exchange Chromatography, Cation Exchange Chromatography, and Mixed Mode Chromatography. In some embodiments, purification of G-CSF includes, but is not limited to, the following steps: Dowex flow-through chromatography, Acid Precipitation/Clarification, Anion Exchange Chromatography, Cation Exchange Chromatography, and Mixed Mode Chromatography.

C. to about 19.degree. C., about 18.degree. C. to about 25.degree. C., about 18.degree. C. to about 24.degree. C., about 18.degree. C. to about 23.degree. C., about 18.degree. C. to about 22.degree. C., about 18.degree. C. to about 21.degree. C., about 18.degree. C. to about 20.degree. C., about 19.degree. C. to about 25.degree. C., about 19.degree. C. to about 24.degree. C., about 19.degree. C. to about 23.degree. C., about 19.degree. C. to about 22.degree. C., about 19.degree. C. to about 21.degree. C., about 20.degree. C. to about 25.degree. C., about 20.degree. C. to about 24.degree. C., about 20.degree. C. to about 23.degree. C., about 20.degree. C. to about 22.degree. C., about 21.degree. C. to about 25.degree. C., about 21.degree. C. to about 24.degree. C., about 21.degree. C. to about 23.degree. C., about 22.degree. C. to about 25.degree. C., about 22.degree. C. to about 24.degree. C., or about 23.degree. C. to about 25.degree. C.).

Anion Exchange Chromatography

[0044] The Anion Exchange Chromatography step of the DSP is used to further purify the r-met-Hu-G-CSF present in the clarified pool by reducing impurities such as host-cell proteins (HCP), DNA, and product-related variants.

[0045] In some embodiments, the chromatography system can be a GE Healthcare BioProcess skid. In some embodiments, the anion exchange resin can be TSKgelDEAE-5PW or Toyopearl DEAE-650M. In some embodiments, the load factor at this step is about 3.6, about 3.8, about 4.0, about 4.2, about 4.4, about 4.6, about 4.8, about 5.0, about 5.2, about 5.4, about 5.6, about 5.8, about 6.0, about 6.2, about 6.4, about 6.6, about 6.8, about 7.0, about 7.2, about 7.4, about 7.6, about 7.8, or about 8.0 g/L resin. In some embodiments, the load factor at this step is about 3.6 g/L resin to about 8.0 g/L resin (e.g., about 3.6 g/L resin to about 7.8 g/L resin, about 3.6 g/L resin to about 7.6 g/L resin, about 3.6 g/L resin to about 7.4 g/L resin, about 3.6 g/L resin to about 7.2 g/L resin, about 3.6 g/L resin to about 7.0 g/L resin, about 3.6 g/L resin to about 6.8 g/L resin, about 3.6 g/L resin to about 6.6 g/L resin, about 3.6 g/L resin to about 6.4 g/L resin, about 3.6 g/L resin to about 6.2 g/L resin, about 3.6 g/L resin to about 6.0 g/L resin, about 3.6 g/L resin to about 5.8 g/L resin, about 3.6 g/L resin to about 5.6 g/L resin, about 3.6 g/L resin to about 5.4 g/L resin, about 3.6 g/L resin to about 5.2 g/L resin, about 3.6 g/L resin to about 5.0 g/L resin, about 3.6 g/L resin to about 4.8 g/L resin, about 3.6 g/L resin to about 4.6 g/L resin, about 3.6 g/L resin to about 4.4 g/L resin, about 3.6 g/L resin to about 4.2 g/L resin, about 3.6 g/L resin to about 4.0 g/L resin, about 3.6 g/L resin to about 3.8 g/L resin, about 4.0 g/L resin to about 8.0 g/L resin, about 4.0 g/L resin to about 7.8 g/L resin, about 4.0 g/L resin to about 7.6 g/L resin, about 4.0 g/L resin to about 7.4 g/L resin, about 4.0 g/L resin to about 7.2 g/L resin, about 4.0 g/L resin to about 7.0 g/L resin, about 4.0 g/L resin to about 6.8 g/L resin, about 4.0 g/L resin to about 6.6 g/L resin, about 4.0 g/L resin to about 6.4 g/L resin, about 4.0 g/L resin to about 6.2 g/L resin, about 4.0 g/L resin to about 6.0 g/L resin, about 4.0 g/L resin to about 5.8 g/L resin, about 4.0 g/L resin to about 5.6 g/L resin, about 4.0 g/L resin to about 5.4 g/L resin, about 4.0 g/L resin to about 5.2 g/L resin, about 4.0 g/L resin to about 5.0 g/L resin, about 4.0 g/L resin to about 4.8 g/L resin, about 4.0 g/L resin to about 4.6 g/L resin, about 4.0 g/L resin to about 4.4 g/L resin, about 4.0 g/L resin to about 4.2 g/L resin, about 5.0 g/L resin to about 8.0 g/L resin, about 5.0 g/L resin to about 7.8 g/L resin, about 5.0 g/L resin to about 7.6 g/L resin, about 5.0 g/L resin to about 7.4 g/L resin, about 5.0 g/L resin to about 7.2 g/L resin, about 5.0 g/L resin to about 7.0 g/L resin, about 5.0 g/L resin to about 6.8 g/L resin, about 5.0 g/L resin to about 6.6 g/L resin, about 5.0 g/L resin to about 6.4 g/L resin, about 5.0 g/L resin to about 6.2 g/L resin, about 5.0 g/L resin to about 6.0 g/L resin, about 5.0 g/L resin to about 5.8 g/L resin, about 5.0 g/L resin to about 5.6 g/L resin, about 5.0 g/L resin to about 5.4 g/L resin, about 5.0 g/L resin to about 5.2 g/L resin, about 6.0 g/L resin to about 8.0 g/L resin, about 6.0 g/L resin to about 7.8 g/L resin, about 6.0 g/L resin to about 7.6 g/L resin, about 6.0 g/L resin to about 7.4 g/L resin, about 6.0 g/L resin to about 7.2 g/L resin, about 6.0 g/L resin to about 7.0 g/L resin, about 6.0 g/L resin to about 6.8 g/L resin, about 6.0 g/L resin to about 6.6 g/L resin, about 6.0 g/L resin to about 6.4 g/L resin, about 6.0 g/L resin to about 6.2 g/L resin, about 7.0 g/L resin to about 8.0 g/L resin, about 7.0 g/L resin to about 7.8 g/L resin, about 7.0 g/L resin to about 7.6 g/L resin, about 7.0 g/L resin to about 7.4 g/L resin, or about 7.0 g/L resin to about 7.2 g/L resin).

[0046] In some embodiments, the process pH (elution) is about 6.8, about 6.9, about 7.0, about 7.1, or about 7.2, or about 6.8 to about 7.2, about 6.8 to about 7.1, about 6.8 to about 7.0, about 6.9 to about 7.2, about 6.9 to about 7.1, or about 7.0 to about 7.2. In some embodiments, the temperature at

this step is controlled in the range of 3-13.degree. C., 4-12.degree. C., or 5-11.degree. C. In some embodiments, the product is eluted over about 5.9 CV, about 6.0 CV, or about 6.1 CV. In embodiments of the invention, the main product eluate pool collection stops when the UV.sub.280 value reaches 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, or 75% of the peak maximum UV.sub.280 value.

Cation Exchange Chromatography

[0047] In some embodiments, a Cation Exchange Chromatography step of the DSP further purifies r-met-Hu-G-CSF by reducing HCP, DNA, and product-related variants present in the Anion Exchange Chromatography pool. In some embodiments where more than one Cation Exchange Chromatography step is used, they may be distinguished by suffix numeral (e.g., Cation Exchange Chromatography 1 and Cation Exchange Chromatography 2).

[0048] In some embodiments, the chromatography system is a GE Healthcare BioProcess skid. In some embodiments, the cation exchange resin is SP Sepharose Fast Flow or CM Sepharose Fast Flow. In some embodiments, the load factor at this step is about 2.3, about 2.4, about 2.5, about 2.6, about 2.7, about 2.8, about 2.9, about 3.0, about 3.1, about 3.2, about 3.3, about 3.4, about 3.5, about 3.6, about 3.7, about 3.8, about 3.9, about 4.0, about 4.1, about 4.2, about 4.3, about 4.4, about 4.5, about 4.6, about 4.7, about 4.8, about 4.9, about 5.0, about 5.1, about 5.2, about 5.3, about 5.4, about 5.5, about 5.6, about 5.7, about 5.8, or about 5.9 g/L resin. In some embodiments, the load factor at this step is about 2.2 g/L resin to about 6.0 g/L resin (e.g., about 2.2 g/L resin to about 5.8 g/L resin, about 2.2 g/L resin to about 5.6 g/L resin, about 2.2 g/L resin to about 5.4 g/L resin, about 2.2 g/L resin to about 5.2 g/L resin, about 2.2 g/L resin to about 5.0 g/L resin, about 2.2 g/L resin to about 4.8 g/L resin, about 2.2 g/L resin to about 4.6 g/L resin, about 2.2 g/L resin to about 4.4 g/L resin, about 2.2 g/L resin to about 4.2 g/L resin, about 2.2 g/L resin to about 4.0 g/L resin, about 2.2 g/L resin to about 3.8 g/L resin, about 2.2 g/L resin to about 3.6 g/L resin, about 2.2 g/L resin to about 3.4 g/L resin, about 2.2 g/L resin to about 3.2 g/L resin, about 2.2 g/L resin to about 3.0 g/L resin, about 2.2 g/L resin to about 2.8 g/L resin, about 2.2 g/L resin to about 2.6 g/L resin, about 2.2 g/L resin to about 2.4 g/L resin, about 3.0 g/L resin to about 6.0 g/L resin, about 3.0 g/L resin to about 5.8 g/L resin, about 3.0 g/L resin to about 5.6 g/L resin, about 3.0 g/L resin to about 5.4 g/L resin, about 3.0 g/L resin to about 5.2 g/L resin, about 3.0 g/L resin to about 5.0 g/L resin, about 3.0 g/L resin to about 4.8 g/L resin, about 3.0 g/L resin to about 4.6 g/L resin, about 3.0 g/L resin to about 4.4 g/L resin, about 3.0 g/L resin to about 4.2 g/L resin, about 3.0 g/L resin to about 4.0 g/L resin, about 3.0 g/L resin to about 3.8 g/L resin, about 3.0 g/L resin to about 3.6 g/L resin, about 3.0 g/L resin to about 3.4 g/L resin, about 3.0 g/L resin to about 3.2 g/L resin, about 4.0 g/L resin to about 6.0 g/L resin, about 4.0 g/L resin to about 5.8 g/L resin, about 4.0 g/L resin to about 5.6 g/L resin, about 4.0 g/L resin to about 5.4 g/L resin, about 4.0 g/L resin to about 5.2 g/L resin, about 4.0 g/L resin to about 5.0 g/L resin, about 4.0 g/L resin to about 4.8 g/L resin, about 4.0 g/L resin to about 4.6 g/L resin, about 4.0 g/L resin to about 4.4 g/L resin, about 4.0 g/L resin to about 4.2 g/L resin, about 5.0 g/L resin to about 6.0 g/L resin, about 5.0 g/L resin to about 5.8 g/L resin, about 5.0 g/L resin to about 5.6 g/L resin, about 5.0 g/L resin to about 5.4 g/L resin, about 5.0 g/L resin to about 5.2 g/L resin).

[0049] In some embodiments, the process pH (elution) is about 5.2, about 5.4, or about 5.6, or about 5.2 to about 5.6, about 5.2 to about 5.4, or about 5.4 to about 5.6. In some embodiments, the temperature at this step is controlled in the range of 3-13.degree. C., 4-12.degree. C., or 5-11.degree. C. In some embodiments, the product is eluted over about 12.4 CV, about 12.5 CV, or about 12.6 CV. In embodiments of the invention, the main product eluate pool collection stops when the UV.sub.280 value reaches 60, 65, 70, 75, or 80% of the peak maximum UV.sub.280 value.

[0050] Mixed Mode Chromatography

[0051] In some embodiments, a Mixed Mode Chromatography step of the DSP is used to purify the r-met-Hu-G-CSF by decreasing product related variants. In some embodiments, the Mixed Mode Chromatography step decreases product related variants present in the Cation Exchange Chromatography 1 in-process pool.

about 5.1, or about 5.2, or about 4.8 to about 5.2, about 4.8 to about 5.0, or about 5.0 to about 5.2. In some embodiments, the reaction time is about 3.75, about 4.00, or about 4.25 hrs, or about 3.5 hours to about 4.5 hours, about 3.5 hours to about 4.0 hours, or about 4.0 hours to about 4.5 hours, and the reaction temperature is about 17.degree. C., about 18.degree. C., about 19.degree. C., about 20.degree. C., about 21.degree. C., about 22.degree. C., or about 23.degree. C., or about 17.degree. C. to about 23.degree. C., about 17.degree. C. to about 22.degree. C., about 17.degree. C. to about 21.degree. C., about 17.degree. C. to about 20.degree. C., about 17.degree. C. to about 19.degree. C., about 18.degree. C. to about 23.degree. C., about 18.degree. C. to about 22.degree. C., about 18.degree. C. to about 21.degree. C., about 18.degree. C. to about 20.degree. C., about 19.degree. C. to about 23.degree. C., about 19.degree. C. to about 22.degree. C., about 19.degree. C. to about 21.degree. C., about 20.degree. C. to about 23.degree. C., about 20.degree. C. to about 22.degree. C., or about 21.degree. C. to about 23.degree. C.

[0060] In some embodiments, the PEGylation reaction by-products can be removed using a second Cation Exchange Chromatography step (Cation Exchange Chromatography 2). In the Cation Exchange Chromatography 2 step of the DSP, the PEGylated protein is purified by removing PEGylation variants present in the PEGylation pool. In some embodiments, the load factor at this step is about 1.6, about 1.7, about 1.8, about 1.9, about 2.0, about 2.1, about 2.2, about 2.3, about 2.4, about 2.5, about 2.6, about 2.7, about 2.8, about 2.9, about 3.0, about 3.1, about 3.2, about 3.3, about 3.4, about 3.5, about 3.6, about 3.7, about 3.8, about 3.9, about 4.0, about 4.1, about 4.2, about 4.3, or about 4.4 g/L resin. In some embodiments, the load factor at this step is about 1.5 g/L resin to about 4.5 g/L resin (e.g., about 1.5 g/L resin to about 4.0 g/L resin, about 1.5 g/L resin to about 3.5 g/L resin, about 1.5 g/L resin to about 3.0 g/L resin, about 1.5 g/L resin to about 2.5 g/L resin, about 1.5 g/L resin to about 2.0 g/L resin, about 2.0 g/L resin to about 4.5 g/L resin, about 2.0 g/L resin to about 4.0 g/L resin, about 2.0 g/L resin to about 3.5 g/L resin, about 2.0 g/L resin to about 3.0 g/L resin, about 2.0 g/L resin to about 2.5 g/L resin, about 2.5 g/L resin to about 4.5 g/L resin, about 2.5 g/L resin to about 4.0 g/L resin, about 2.5 g/L resin to about 3.5 g/L resin, about 2.5 g/L resin to about 3.0 g/L resin, about 3.0 g/L resin to about 4.5 g/L resin, about 3.0 g/L resin to about 4.0 g/L resin, about 3.0 g/L resin to about 3.5 g/L resin, about 3.5 g/L resin to about 4.5 g/L resin, about 3.5 g/L resin to about 4.0 g/L resin, or about 4.0 g/L resin to about 4.5 g/L resin). In embodiments of the invention, the process pH (elution) is about 5.2, about 5.4, or about 5.6, or about 5.2 to about 5.6, about 5.2 to about 5.4, or about 5.4 to about 5.6. In some embodiments, the gradient length, in CVs, is about 8.3, about 8.4, or about 8.5. In embodiments of the invention, the main product eluate pool collection stops when the UV.sub.280 value reaches 30, 35, or 40% of the peak maximum UV.sub.280 value.

Bulk Formulation and Fill

[0061] The Formulation and Fill step of the DSP is to ensure that the drug substance expressed product achieves the specified concentration and is filled into clean certified sterile containers. In some embodiments, the formulation is adjusted so that the r-met-Hu-G-CSF is present at about 10 mg/mL. In some embodiments, the drug product is filled into a sterile syringe.

Buffers

[0062] Buffers are prepared in a batch process where components are dispensed into a defined quantity of water and mixed to homogeneity, 0.2-.mu.m filtered, and stored according to approved site procedures. Product-contacting buffers and solutions for process steps prior to mixed mode chromatography are prepared using purified water (PW). Product-contacting buffers and solutions for process steps from Mixed Mode Chromatography through Formulation/Fill can be prepared using water for injection (WFI). Each buffer has defined composition limits and can be controlled for ingredient weight and pH per buffer batch records. Any buffer not meeting its release criteria can be discarded. Routine processing can be performed at controlled room temperature (17.degree. C.-23.degree. C.). Product pool bioburden and endotoxin samples can be taken at the end of the pool hold duration prior to 0.2-.mu.m filtration.

[0063] Any patents, patent publications, and applications, and all documents cited therein or during their prosecution ("appin cited documents") and all documents cited or referenced in the appin cited documents, together with any instructions, descriptions, product specifications, and product sheets for any products mentioned therein or in any document therein and incorporated by reference herein, are hereby incorporated herein by reference, and may be employed in the practice of the invention. All documents (e.g., these patents, patent publications and applications and the appin cited documents) are incorporated herein by reference to the same extent as if each individual document was specifically and individually indicated to be incorporated by reference.

[0064] The present invention will be further illustrated in the following Examples which are given for illustration purposes only and are not intended to limit the invention in any way.

EXAMPLES

Example 1: Shake Flask Primary Inoculum

[0065] The inoculum step of the UP process uses kanamycin in the medium to maintain selective pressure and does not include product induction. The primary inoculum is a shake flask culture, initiated with two WCB vials. The vials are removed from -70.degree. C. storage, thawed, and at least 200 .mu.L of each vial is inoculated into each of the six 4-L shake flasks, each of which contains 1.2 L of medium containing 20.0 g/L Select APS LB Broth Base and 0.05 g/L of kanamycin sulfate. The flasks are incubated in a shaking incubator at 230-270 revolutions per minute (rpm) and 30.degree. C. Incubator agitation and temperature are monitored and controlled.

[0066] Optical density (OD600) measurements are taken until the individual flask cell masses reach an OD600 .gtoreq.2.8. The entire contents of the six shake flasks are then pooled in a biosafety cabinet into a pressure can and tested to verify the pooled cell mass reached an OD600 of .gtoreq.2.8. The pressure can can be immediately transported by personnel to the production bioreactor. The pooled contents are tested for host cell purity. Exemplary process parameters for the Shake Flask Primary Inoculum Process are indicated below in Table 1.

TABLE-US-00001 TABLE 1 Unit of Normal Operating Process Parameter Measure Range Medium quantity kg 1.19-1.21 Agitation rpm 230-270 Temperature .degree. C. 28-32

Example 2: Production Fermentation

[0067] The production (batch) medium is prepared in the fermentor at a target volume of 1,100 L. The medium comprises yeast extract and glycerol, which are heat sterilized in the fermentor, as well as antifoam, kanamycin, and trace elements that are 0.2-.mu.m filtered into the fermentor as soon as it has cooled down to ambient temperature. This medium is batched and sterilized in the fermentor. The production fermentor is inoculated by connecting the primary inoculum pressure can to the fermentor via a steam sterilized transfer line. The pressure can contents are transferred to the production fermentor via a pressurization of the can with filtered process air.

[0068] During the growth phase, the production culture is controlled at 36.5-37.5.degree. C. and pH 6.6-7.0. Phosphoric acid and ammonium hydroxide are used to maintain pH control. At 6.5 hours post-inoculation (or immediately following a DO spike due to carbon limitation), a time-based nutrient feed medium addition with 9 individual feed stages at specific flow rates ranging from 20 kg/hr to 35 kg/hr for durations of 30 to 60 minutes begins. The duration of the last feed stage is through the completion of fermentation.

[0069] For the nutrient feed medium preparation, a glucose solution is prepared in a feed tank and heat sterilized. After this solution has cooled to ambient temperature, yeast extract, magnesium sulfate, ammonium sulfate, citric acid, and methionine and leucine supplements are transferred to the feed tank through a 0.2- μm filter.

[0070] The culture temperature is reduced to 34.degree. C. at 6.5 hours after the start of the feed medium addition. Product formation is induced at 7 hours after the initiation of feed addition, by adding IPTG solution, corresponding to a broth concentration of 1.3 mM IPTG based on initial bioreactor volume. The IPTG solution is transferred into the bioreactor from a pressurized stainless-steel can connected through a 0.2- μm sterilizing filter. At 6 hours post-induction, the culture is chilled to 12.degree. C. in preparation for harvest. Throughout the production fermentation stage, optical density (OD600) values are taken to monitor cell growth. In some embodiments, the production culture duration may not exceed 21 hours. In some embodiments, the total culture duration, defined as vial thaw to initiation of harvest, may not exceed 55 hours and 15 minutes. At the end of the culture, aseptic samples are taken for product concentration (titer) and IPC testing. Titrers are typically >1.3 g/L. Exemplary process parameters for the Production Fermentation stage are provided in Table 2 below:

TABLE-US-00002 TABLE 2 Unit of Normal Operating Process Parameter Measure Range Agitation rpm 50-190 pH N/A 6.6-7.0 Temperature (pre-induction) .degree. C. 36.5-37.5 Temperature (at induction) .degree. C. 33.5-34.5 Dissolved oxygen % 15-55 Feed start time (duration from hh:mm 06:20-06:40 inoculation) Induction start (duration from hh:mm 06:45-07:15 feed start) Induction duration hh:mm 05:45-06:15 Production culture duration hh:mm .ltoreq.21:00 Maximum total culture duration hh:mm .ltoreq.55:15

Example 3: Cell Harvest

[0071] The purpose of the Cell Harvest stage is to separate and retain cells from the liquid phase of the culture. The solid phase (cells) of the whole culture broth is separated from the liquid phase by centrifugation using, e.g., a disc-stack centrifuge. The centrifuge discharge is connected to a 2,000-L stainless-steel jacketed collection vessel via a stainless-steel transfer line. The separated solids (cell paste) accumulate in the bowl and are discharged at 20-L intervals and transferred to a collection vessel maintained at .ltoreq.15.degree. C. During centrifugation, the feed flow rate to the centrifuge is maintained at 11.0 L/min, the bowl speed of approximately 7500 rpm, and the centrate back pressure at 50 pounds per square inch gauge (psig). Once the production culture has been processed through the centrifuge, the harvested cell paste can be diluted with purified water to 1,575 kg total pool mass. Exemplary process parameters for the Cell Harvest step are provided in Table 3 below. The cell paste can be forward-processed without interruption to the Cell Lysis step.

TABLE-US-00003 TABLE 3 Unit of Normal Operating Process Parameter Measure Range Centrifuge feed flow rate L/min 9.0-12.0 Centrifuge backpressure psig 45-55 (centrate) Discharge interval L 16-21 Post-dilution pool mass kg 1550-1600

Example 4: Cell Lysis

[0072] The purpose of the Cell Lysis stage is to mechanically rupture the cells to release the inclusion bodies. The cell paste feed vessel can be connected to a high-pressure homogenizer via a stainless-steel transfer line. Towards the end of the cell paste transfer, purified water is used to chase residual cell paste from the feed vessel. The homogenizer outlet is connected to a heat exchanger which feeds to a 2,000-L stainless-steel lysate collection tank. The diluted cell paste is passed through the homogenizer at least three times at a pressure of 885 bar and flow rate of 8.5 L/min. The lysate temperature can be maintained at .ltoreq.15.degree. C. by a heat exchanger at the outlet of the homogenizer and temperature control of the collection vessel jacket. If the lysate pool mass is less than 1,590 kg, purified water can be added to the pool to achieve a mass of 1,590 kg.

Exemplary process parameters for the Cell Lysis step are provided in Table 4 below. The lysate pool can be forward-processed without interruption to

the Inclusion Body Harvest step.

TABLE-US-00004 TABLE 4 Unit of Normal Operating Process Parameter Measure Range Flow rate L/min 6.0-10.0 Break pressure bar 860-910 Lysate temperature .degree. C. .ltoreq.15

Example 5: Inclusion Body Harvest and Wash

[0073] The purpose of the Inclusion Body Harvest and Wash step of the UP is to separate the IBs from the liquid phase of the cell lysate and to remove cell debris. The lysate-containing feed vessel is connected to the disc-stack centrifuge via a stainless-steel transfer line. The centrifuge discharge is connected via a stainless-steel transfer line to the 2,000-L stainless-steel inclusion body collection tank. The separated solids accumulate in the centrifuge bowl and are discharged at 120-L intervals and transferred to a collection vessel maintained at .ltoreq.15.degree. C. The liquid phase is sent to process waste. During centrifugation, the centrifuge feed flow rate is maintained at 8.0 L/min, the bowl speed at approximately 7500 rpm, and the centrate backpressure at 50 psig. Exemplary process parameters for the Inclusion Body Harvest are provided in Table 5 below.

TABLE-US-00005 TABLE 5 Unit of Normal Operating Process Parameter Measure Range Centrifuge feed flow rate L/min 4.0-10.0 Centrifuge Backpressure psig 45-55 (centrate) Discharge interval L 105-122

[0074] The resulting inclusion body paste can then be re-suspended with purified water to the requisite total pool mass and processed through the centrifuge a second time to further remove cell debris. The solids accumulate in the bowl and are discharged at 136-L intervals and transferred via a stainless-steel line to a single-use mixing vessel maintained at .ltoreq.20.degree. C. The feed flow rate and centrate backpressure are maintained within the ranges disclosed. The harvested WIB are dispensed as 5-L aliquots into single-use bags. Each bag is labeled and numbered and transported by production personnel to a controlled storage area where they are placed into freezers for storage at <-60.degree. C. for up to 24 months. Exemplary process parameters for the WIB process are provided in Table 6 below.

TABLE-US-00006 TABLE 6 Unit of Normal Operating Process Parameter Measure Range Post-dilution pool mass kg 1576-1624 Centrifuge feed flow rate L/min 4.0-10.0 Centrifuge backpressure psig 45-55 (centrate) Centrifuge bowl speed rpm 7188-7788 Discharge interval L 120-138 Bag fill volume L <6 Bag storage temperature .degree. C. .ltoreq.-60 Bag storage duration months .ltoreq.24

Example 6: WIB Thaw/Solubilization/Oxidation

[0075] In the WIB thaw phase, the frozen inclusion bodies can be thawed by static incubation at 17-23.degree. C. for no more than 36 hours. For the Solubilization phase, the solubilization solution is prepared in a 550-L stainless-steel tank. A mass of thawed WIB containing 1188-1212 g of the expressed r-met-Hu-G-CSF (IB product mass) is transferred into the solubilization solution through a silicone tubing transfer line using a peristaltic pump and is mixed for 1.5-2.5 hours. The final buffer composition of the solubilization solution is in the range of about 8 to about 11 g/L (e.g., about 8 g/L to about 10.5 g/L, about 8 g/L to about 10 g/L, about 8 g/L to about 9.5 g/L, about 8 g/L to about 9 g/L, about 8 g/L to about 8.5 g/L, about 8.5 g/L to about 11 g/L, about 8.5 g/L to about 10.5 g/L, about 8.5 g/L to about 10 g/L, about 8.5 g/L to about 9.5 g/L, about 8.5 g/L to about 9 g/L, about 9 g/L to about 11 g/L, about 9 g/L to about 10.5 g/L, about 9 g/L to about 10 g/L, about 9 g/L to about 9.5 g/L, about 9.5 g/L to about 11 g/L, about 9.5 g/L to about 10.5 g/L, about 9.5 g/L to about 10 g/L, about 10 g/L to about 11 g/L, about 10 g/L to about 10.5 g/L, or about 10.5 g/L to about 11 g/L) Sarkosyl, about 15 to about 35 mM (e.g., about 15 mM to about 30 mM, about 15 mM to about 25 mM, about 15 mM to about 20 mM, about 20 mM to about 35 mM, about 20 mM to about 30 mM, about 20 mM to about 25 mM, about 25 mM to about 35 mM, about 25 mM to about 30 mM, or about 30 mM to about 35 mM) Tris, pH of about 7 to about 8.5 (e.g., about 7 to about 8.4, about 7 to about 8.2, about 7 to about 8, about 7 to about

7.8, about 7 to about 7.6, about 7 to about 7.4, about 7 to about 7.2, about 7.2 to about 8.5, about 7.2 to about 8.4, about 7.2 to about 8.2, about 7.2 to about 8, about 7.2 to about 7.8, about 7.2 to about 7.6, about 7.2 to about 7.4, about 7.4 to about 8.5, about 7.4 to about 8.4, about 7.4 to about 8.2, about 7.4 to about 8, about 7.4 to about 7.8, about 7.4 to about 7.6, about 7.6 to about 8.5, about 7.6 to about 8.4, about 7.6 to about 8.2, about 7.6 to about 8, about 7.6 to about 7.8, about 7.8 to about 8.5, about 7.8 to about 8.4, about 7.8 to about 8.2, about 7.8 to about 8, about 8 to about 8.5, about 8 to about 8.4, about 8 to about 8.2, about 8.2 to about 8.5, or about 8.2 to about 8.4). The target product concentration in the Solubilization pool is 4.5-5.5 g/L. The total volume of the Solubilization phase can be approximately 240 L.

[0076] After the end of the Solubilization period, the Oxidation phase begins disulfide bond formation by adding 20 mM copper sulfate stock solution to achieve a final concentration of 200 μ M copper. The refold process is controlled at pH in the range of 7.8-8.2 and at temperature in the range of 17-23.degree. C. To verify completion of the refold progress, samples are taken at regular intervals and assessed by reversed-phase high-performance liquid chromatography (RPC). The non-reduced peak area is measured in 2-hour intervals. The reaction is considered complete when the difference between non-reduced peak areas of two consecutive time points is lower than 4%. At the completion of the refold process, a stock solution of 12 mM ethylenediaminetetraacetic acid (EDTA) is added to achieve a final concentration of 600 μ M EDTA in order to quench the refold reaction. In some embodiments, the maximum time from completion of the oxidation step until the subsequent Dowex step is 24 hours at 17-23.degree. C.

Example 7: Dowex Chromatography

[0077] The solubilization/oxidation pool is passed over the Dowex chromatography resin where the Sarkosyl is captured and the product is collected in the flow-through effluent. Prior to each downstream batch, the Dowex anion exchange resin is packed with resin mass and the packing density of Dowex resin results in a packed bed height of 40-50 cm. The packed column can be sanitized prior to use with successive washes of 4 column volumes (CV) of 1.0 M acetic acid, 5 CV of purified water (PW), and 3 CV of 1.0 M sodium hydroxide. The column can be held in 1.0 M NaOH for a minimum of 12 hours. The sanitization phase can be followed by another 5 CV PW flush.

[0078] After column sanitization, the packed column can be pre-equilibrated with 3 CV of 0.4 M Tris, 0.5 M NaCl, pH 8.0 to facilitate equilibration. The subsequent equilibration phase can be a 3 CV flush with a 20 mM Tris, pH 8.0 buffer. Before loading the column, the Solubilization/Oxidation pool can be diluted with purified water to four times the pool mass. This is accomplished by transferring the quenched Solubilization/Oxidation pool from the Solubilization/Oxidation tank through a stainless-steel transfer line into a 2,250-L stainless-steel tank using air pressure, after which 3 volumes of purified water are added to the 2,250-L tank.

[0079] The Dowex load is pumped onto the column taking into account the Sarkosyl load factor. The Sarkosyl binds to the resin as the product flows through to the collection tank. Product collection starts with the beginning of product load and ends after a 1 CV flush with 20 mM Tris, pH 8.0 after the load is complete. The eluate and flush are collected in a 2,250-L stainless-steel tank through a stainless-steel transfer line. Product pooling is controlled volumetrically, therefore monitoring of the column eluate for UV absorbance is not performed. The single-use Dowex resin is discarded and a new column is packed prior to the next run. In some embodiments, the maximum time from completion of the Dowex step until the subsequent Acidification/Clarification step is at most 8 hours at 17-23.degree. C. Exemplary process parameters for the Dowex Chromatography step are provided in Table 7 below.

TABLE-US-00007 TABLE 7 Unit of Normal Operating Process Parameter Measure Range Resin mass kg 22.6-23.0 Load factor g Sarkosyl/ 72-78 L resin Temperature .degree. C. 17-23 Load/wash flow rate L/min 1.5-1.9 Start collect CV after N/A load start End collect CV after 0.9-1.1 start of wash Dowex pool hold temperature .degree. C. 17-23 Dowex pool hold duration hours .ltoreq.8

Example 8: Acid Precipitation/Clarification

[0080] The purpose of this step of the DSP is to decrease the levels of host-cell derived impurities from the product stream to prepare for anion exchange chromatography. The Dowex pool is titrated to a pH in the range of 4.3-4.7 with 1.0 M acetic acid. The acidified pool is mixed for 15-25 minutes at 17-23.degree. C. The liquid phase of the acidified pool containing product can then be separated from the solid phase (waste) by centrifugation using a disc-stack centrifuge. The feed flow rate can be maintained at 14-16 L/min at a bowl speed of approximately 7500 rpm and with a centrate backpressure of 45-55 psig. The accumulated solids are discharged at a 225-L interval and discarded. The clarified centrate can be transferred from the centrifuge to a 2,250-L stainless-steel collection tank via a stainless-steel transfer line. The clarified pool can then be titrated with 1.0 N sodium hydroxide. In some embodiments, the maximum time from completion of the Clarification phase until the subsequent Anion Exchange Chromatography step is 16 hours at 17-23.degree. C. Exemplary process parameters for the Acid Precipitation/Clarification step are provided in Table 8 below.

TABLE-US-00008 TABLE 8 Unit of Normal Operating Process Parameter Measure Range Acidification pH pH 4.3-4.7 Acidification temperature .degree. C. 17-23 Acidification mixing speed RPM 100-120 Acidified pool mix time minutes 15-25 Centrifuge feed flow rate L/min 14-16 Centrifuge backpressure (centrate) psig 45-55 Clarified pool pH pH 7.8-8.2 Clarified pool hold temperature .degree. C. 7-13 Clarified pool hold duration hours .ltoreq.16

Example 9: Anion Exchange Chromatography

[0081] In this step, the anion exchange resin in the chromatography system is packed in a 60-cm diameter column to a bed height of 40 cm. Prior to each use, the column can be flushed with 2 CV 0.1 M sodium hydroxide (NaOH) and sanitized with 3 CV of 1.0 N NaOH with a sanitization hold duration of at least 30 minutes at 20.degree. C. The 1.0 N NaOH can be flushed out of the column with 2.0 CV of 0.1 N NaOH. The residence time for all chromatography phases can be 14.0 min/CV with the exception of the elution phase, which can be run at a lower flow rate, equivalent to a 22.4 min/CV residence time.

[0082] To facilitate equilibration, the sanitized column can be pre-equilibrated and then equilibrated with 3 CV of 20 mM Tris pH 8.0 buffer. From column equilibration through elution, the feed stream going to the column can be passed through a heat exchanger. The temperature can be controlled during the product-contacting phases. The clarified pool can be depth filtered and 0.2-.mu.m filtered in-line prior to loading onto the column at a load factor in the range of about 3.6 g/L to about 8.0 g/L (e.g., about 3.6 g/L to about 7.5 g/L, about 3.6 g/L to about 7.0 g/L, about 3.6 g/L to about 6.5 g/L, about 3.6 g/L to about 6.0 g/L, about 3.6 g/L to about 5.5 g/L, about 3.6 g/L to about 5.0 g/L, about 3.6 g/L to about 4.5 g/L, about 3.6 g/L to about 4.0 g/L, about 4.0 g/L to about 8.0 g/L, about 4.0 g/L to about 7.5 g/L, about 4.0 g/L to about 7.0 g/L, about 4.0 g/L to about 6.5 g/L, about 4.0 g/L to about 6.0 g/L, about 4.0 g/L to about 5.5 g/L, about 4.0 g/L to about 5.0 g/L, about 4.0 g/L to about 4.5 g/L, about 4.5 g/L to about 8.0 g/L, about 4.5 g/L to about 7.5 g/L, about 4.5 g/L to about 7.0 g/L, about 4.5 g/L to about 6.5 g/L, about 4.5 g/L to about 6.0 g/L, about 4.5 g/L to about 5.5 g/L, about 4.5 g/L to about 5.0 g/L, about 5.0 g/L to about 8.0 g/L, about 5.0 g/L to about 7.5 g/L, about 5.0 g/L to about 7.0 g/L, about 5.0 g/L to about 6.5 g/L, about 5.0 g/L to about 6.0 g/L, about 5.0 g/L to about 5.5 g/L, about 5.5 g/L to about 8.0 g/L, about 5.5 g/L to about 7.5 g/L, about 5.5 g/L to about 7.0 g/L, about 5.5 g/L to about 6.5 g/L, about 5.5 g/L to about 6.0 g/L, about 6.0 g/L to about 8.0 g/L, about 6.0 g/L to about 7.5 g/L, about 6.0 g/L to about 7.0 g/L, about 6.0 g/L to about 6.5 g/L, about 6.5 g/L to about 8.0 g/L, about 6.5 g/L to about 7.5 g/L, about 6.5 g/L to about 7.0 g/L, about 7.0 g/L to about 8.0 g/L, about 7.0 g/L to about 7.5 g/L, or about 7.5 g/L to about 8.0 g/L) of resin. After loading, the column is washed with 3 CV of 20 mM Tris, pH 7.0 buffer. The product can then be eluted using a linear gradient of increasing ionic strength, e.g., from 20 mM Tris pH 7.0 to 20 mM Tris, 100 mM NaCl, pH 7.0 over 5.9-6.1 CV.

[0083] In-process pool collection is achieved by fractionation of the product peak. The start and end of pooling is based on absorbance at 280 nm. When the UV.sub.280 peak reaches .gtoreq.0.25 AU/cm, two 20-L fractions of eluate are collected into sterile single-use bags, prior to the collection of the main product peak fraction. The main product eluate pool collection stops when the UV.sub.280 value reaches 65-75% of the peak maximum UV.sub.280 value. The main product peak fraction is also collected in a sterile single-use bag. Once the peak maximum is known, the contents of 20-L fractions with initial (at the start of fraction collection) UV.sub.280 values above 15% of peak maximum are combined with the main product fraction after the elution is complete.

[0084] The column can be cleaned with a non-denaturing ionic solution (2 CV of 2 M NaCl) followed by a sanitization with 3 CV of denaturing alkaline solution, 1 M NaOH, with a minimum sanitization duration of 30 minutes at 20.degree. C. If the column is stored for up to two weeks (short-term storage), the column is then flushed with 3 CV of 0.1 M NaOH. If the column is stored for longer than two weeks (long-term storage), it is flushed with 3 CV of 0.4 M Tris, 0.5 M sodium chloride, pH 8.0, followed by a 3 CV flush with 1% benzyl alcohol storage solution. Exemplary process parameters for the Anion Exchange Chromatography step are provided in Table 9 below.

TABLE-US-00009 TABLE 9 Unit of Normal Operating Process Parameter Measure Range Load factor g/L resin 3.6-8.0 Process pH (elution) pH 6.8-7.2 Bed height cm 38-42 Residence time (load/wash) Min/CV 13.3-14.7 Residence time (elution) Min/CV 21.3-23.5 Temperature .degree. C. 4-12 Gradient length CV 5.9-6.1 Start collect UV.sub.280% peak .gtoreq.15 maximum Stop collect UV.sub.280% peak 65-75 maximum Pool hold temperature .degree. C. 2-8 Pool hold duration hh:mm .ltoreq.19:29

Example 10: Cation Exchange Chromatography 1

[0085] The cation exchange resin in the chromatography system is packed in a 60-cm diameter column with a bed height of 40 cm. All chromatography phases are run at the same residence time of 22.6 min/CV. Prior to each use, the column can be flushed with 2 CV 0.1 M NaOH and sanitized with 3 CV of 1.0 M sodium hydroxide. The sanitization hold duration can be at least 30 minutes at 20.degree. C. The sanitization phase can be followed by another flush with 2 CV of 0.1 M NaOH.

[0086] To facilitate equilibration, the sanitized column can be pre-equilibrated with 1.5 CV of 1.0 M sodium acetate, 1.0 M NaCl, pH 5.4 buffer. This phase can be followed by an equilibration with 3 CV of 20 mM sodium acetate, pH 5.4 buffer. Before loading the cation exchange column, the Anion Exchange Chromatography pool can be diluted with 2 pool volumes of 20 mM acetate, pH 5.4. If required, the diluted pool can then be titrated with glacial acetic acid to pH 5.4. From column equilibration through elution, the process stream going to the column can be passed through a heat exchanger to reduce the temperature to 4-12.degree. C. The temperature can be controlled within 4-12.degree. C. during the product-contacting phases.

[0087] The diluted Anion Exchange Chromatography pool can be 0.2-.mu.m filtered in-line prior to loading onto the column at a load factor in the range of about 2.3 g/L to about 5.9 g/L (e.g., about 2.3 g/L to about 5.5 g/L, about 2.3 g/L to about 5.0 g/L, about 2.3 g/L to about 4.5 g/L, about 2.3 g/L to about 4.0 g/L, about 2.3 g/L to about 3.5 g/L, about 2.3 g/L to about 3.0 g/L, about 2.3 g/L to about 2.5 g/L, about 2.5 g/L to about 5.9 g/L, about 2.5 g/L to about 5.5 g/L, about 2.5 g/L to about 5.0 g/L, about 2.5 g/L to about 4.5 g/L, about 2.5 g/L to about 4.0 g/L, about 2.5 g/L to about 3.5 g/L, about 2.5 g/L to about 3.0 g/L, about 3.0 g/L to about 5.9 g/L, about 3.0 g/L to about 5.5 g/L, about 3.0 g/L to about 5.0 g/L, about 3.0 g/L to about 4.5 g/L, about 3.0 g/L to about 4.0 g/L, about 3.0 g/L to about 3.5 g/L, about 3.5 g/L to about 5.9 g/L, about 3.5 g/L to about 5.5 g/L, about 3.5 g/L to about 5.0 g/L, about 3.5 g/L to about 4.5 g/L, about 3.5 g/L to about 4.0 g/L, about 4.0 g/L to about 5.9 g/L, about 4.0 g/L to about 5.5 g/L, about 4.0 g/L to about 5.0 g/L, about 4.0 g/L to about 4.5 g/L, about 4.5 g/L to about 5.9 g/L, about 4.5 g/L to about 5.5 g/L, about 4.5 g/L to about 5.0 g/L, about 5.0 g/L to about 5.9 g/L, about 5.0 g/L to about 5.5 g/L, or about 5.5 g/L to about 5.9 g/L) of resin. After loading, the column can be

washed with 3 column volumes of 20 mM sodium acetate buffer, pH 5.2-5.6, and then eluted using a linear gradient of increasing ionic strength over 12.4-12.6 column volumes. In-process pool collection is achieved by fractionation of the product peak. All fractions are collected in sterile single use bags. The start and end of pooling is based on absorbance at 280 nm. When the UV.sub.280 peak reaches .gtoreq.0.25 AU/cm, two 20-L fractions of eluate are collected into sterile single-use bags, prior to the collection of the main product peak fraction. The main product eluate pool collection stops when the UV.sub.280 value reaches 60-80% of the peak maximum UV.sub.280 value. Once the peak maximum is known, the contents of 20-L fractions with initial (at the start of fraction collection) UV.sub.280 values above 15% of peak maximum are combined with the main product fraction after the elution is complete.

[0088] The column can be cleaned with a non-denaturing ionic solution (2 CV of 1.0 M NaCl) followed by a sanitization with 3 CV of denaturing alkaline solution, 1.0 M NaOH, with a minimum sanitization duration of 30 minutes at 20.degree. C. The column can then be flushed with 3 CV of 0.1 M NaOH and stored until the next use. Exemplary process parameters for Cation Exchange Chromatography 1 step are provided in Table 10 below.

TABLE-US-00010 TABLE 10 Unit of Normal Operating Process Parameter Measure Range Load factor g/L resin 2.3-5.9 Process pH (elution) pH 5.2-5.6 Bed height cm 38-42 Residence time (load/ min/CV 21.5-23.7 wash/elution) Temperature .degree. C. 4-12 Gradient Length CV 12.4-12.6 Start collect UV.sub.280% peak .gtoreq.15 maximum Stop collect UV.sub.280% peak 60-80 maximum Pool hold temperature .degree. C. 2-8 Pool hold duration hh:mm .ltoreq.14:16

Example 11: Mixed Mode Chromatography

[0089] The mixed-mode resin in the chromatography system is packed in a 60-cm diameter column with a bed height of 15 cm. The residence time for all chromatography phases up to elution can be maintained at 7.0 min/CV. For the elution, post-elution cleaning and storage phase, the flow rate can be lowered to a 10.0 min/CV residence time. The Mixed Mode Chromatography step can be run at 20.degree. C.

[0090] Prior to each use, the column can be flushed with 2 CV 0.1M NaOH and sanitized with 3 CV of 1.0 N sodium hydroxide with a sanitization duration of at least 30 minutes. This can be followed by a flush with 2 CV of 0.1N NaOH. To facilitate equilibration, the sanitized column can be pre-equilibrated with 3 CV of 100 mM acetic acid. It can then be equilibrated with 4 CV of 20 mM sodium acetate, 120 mM sodium chloride, pH 5.4 buffer.

[0091] After equilibration, the Cation Exchange Chromatography 1 pool can be 0.2-.mu.m filtered in-line prior to loading onto the column at a load factor in the range of about 5.1 g/L to about 13.3 g/L (e.g., about 5.1 g/L to about 13.0 g/L, about 5.1 g/L to about 12.0 g/L, about 5.1 g/L to about 11.0 g/L, about 5.1 g/L to about 10.0 g/L, about 5.1 g/L to about 9.0 g/L, about 5.1 g/L to about 8.0 g/L, about 5.1 g/L to about 7.0 g/L, about 5.1 g/L to about 6.0 g/L, about 6.0 g/L to about 13.3 g/L of resin, about 6.0 g/L to about 13.0 g/L, about 6.0 g/L to about 12.0 g/L, about 6.0 g/L to about 11.0 g/L, about 6.0 g/L to about 10.0 g/L, about 6.0 g/L to about 9.0 g/L, about 6.0 g/L to about 8.0 g/L, about 6.0 g/L to about 7.0 g/L, about 7.0 g/L to about 13.3 g/L of resin, about 7.0 g/L to about 13.0 g/L, about 7.0 g/L to about 12.0 g/L, about 7.0 g/L to about 11.0 g/L, about 7.0 g/L to about 10.0 g/L, about 7.0 g/L to about 9.0 g/L, about 7.0 g/L to about 8.0 g/L, about 8.0 g/L to about 13.3 g/L of resin, about 8.0 g/L to about 13.0 g/L, about 8.0 g/L to about 12.0 g/L, about 8.0 g/L to about 11.0 g/L, about 8.0 g/L to about 10.0 g/L, about 8.0 g/L to about 9.0 g/L, about 9.0 g/L to about 13.3 g/L of resin, about 9.0 g/L to about 13.0 g/L, about 9.0 g/L to about 12.0 g/L, about 9.0 g/L to about 11.0 g/L, about 9.0 g/L to about 10.0 g/L, about 10.0 g/L to about 13.3 g/L of resin, about 10.0 g/L to about 13.0 g/L, about 10.0 g/L to about 12.0 g/L, about 10.0 g/L to about 11.0 g/L, about 11.0 g/L to about 13.3 g/L of resin, about 11.0 g/L to about 13.0 g/L, about 11.0 g/L to about 12.0 g/L, about 12.0 g/L to about 13.3 g/L of resin, about 12.0 g/L to about 13.0 g/L, or about 13.0 g/L to about 13.3 g/L). After loading, the column can be washed with 3 CV of equilibration buffer. Following the wash

Example 13: PEGylation

[0097] During the PEGylation step, an aldehyde modified PEG molecule (mPEG-aldehyde) is covalently attached to the N-terminus of the r-met-Hu-G-CSF protein to form PEGylated r-met-Hu-G-CSF. The protein is coupled with PEG, followed by reduction with sodium cyanoborohydride at a concentration of 20 mM to form a stable covalent bond between the PEG and protein.

[0098] The process step begins by preparing the PEGylation stock solution in a sterile single-use bag that is used as the reaction vessel. The PEGylation stock solution is a mixture of 50 g/L mPEG-aldehyde in UF/DF 1 diafiltration buffer (100 mM sodium acetate, pH 5.0). The UF/DF 1 product pool is then added to the vessel and the protein-PEG-aldehyde solution is allowed to mix for at least 15 minutes. Then, a 5 M sodium cyanoborohydride stock solution is added to achieve a final cyanoborohydride concentration of 20 mM, and the combined solution is mixed in the range of 17-23.degree. C. and within a pH 4.7-5.3 for 3.75-4.25 hours.

[0099] After the specified reaction time, the reaction mixture can be added to WFI to dilute the mixture and slow the reaction. 1 L of reaction mixture can be added for every 3 L of WFI. The dilution can be performed using a sterile single-use bag as the holding vessel, and liquid transfer can be performed using a peristaltic pump. In some embodiments, the diluted pool can be immediately forward processed to the Cation Exchange Chromatography 2 step. Exemplary process parameters for the PEGylation are provided in Table 13 below.

TABLE-US-00013 TABLE 13 Unit of Normal Operating Process Parameter Measure Range Reaction pH pH 4.8-5.2 PEG:protein ratio g/g 4.7-5.3
Reaction time (from sodium hr 3.75-4.25 cyanoborohydride stock solution addition to addition of WFI) Reaction temperature .degree. C. 17-23
Reaction agitation speed rpm 240-260

Example 14: Cation Exchange Chromatography 2

[0100] The Cation Exchange Chromatography 2 step purifies the PEGylated protein by removing PEGylation variants present in the PEGylation pool. The cation exchange resin in the chromatography system is packed in a 60-cm diameter column with a bed height of 25 cm. The temperature throughout this process step can be 20.degree. C. Prior to each use, the column can be flushed with 2 CV of 0.1 N NaOH and sanitized with 3 CV of 1.0 N NaOH with a minimum sanitization time of 30 minutes. It can then be flushed with 2 CV of 0.1 N NaOH. The pre-use sanitization phases can be run at a residence time of 7.8 min/CV.

[0101] To facilitate equilibration, the sanitized column can be pre-equilibrated with 1.5 CV of 1 M sodium acetate, 1 M NaCl, pH 5.2-5.6 buffer. The equilibration phase can include a 3 CV flush of the column with 20 mM sodium acetate, pH 5.2-5.6. Both pre-equilibration and equilibration can be run at a flow rate equivalent of a 7.8 min/CV residence time. After equilibration, the diluted PEGylation pool can be 0.2- μ m filtered in-line prior to loading. The diluted pool can be loaded onto the column at a load factor in the range of about 1.6 g/L to about 4.4 g/L (e.g., about 1.6 g/L to about 4.0 g/L, about 1.6 g/L to about 3.5 g/L, about 1.6 g/L to about 3.0 g/L, about 1.6 g/L to about 2.5 g/L, about 1.6 g/L to about 2.0 g/L, about 2.0 g/L to about 4.4 g/L, about 2.0 g/L to about 4.0 g/L, about 2.0 g/L to about 3.5 g/L, about 2.0 g/L to about 3.0 g/L, about 2.0 g/L to about 2.5 g/L, about 2.5 g/L to about 4.4 g/L, about 2.5 g/L to about 4.0 g/L, about 2.5 g/L to about 3.5 g/L, about 2.5 g/L to about 3.0 g/L, about 3.0 g/L to about 4.4 g/L, about 3.0 g/L to about 4.0 g/L, about 3.0 g/L to about 3.5 g/L, about 3.5 g/L to about 4.4 g/L, about 3.5 g/L to about 4.0 g/L, or about 4.0 g/L to about 4.4 g/L) of resin. The residence time during the load, wash, and elution phases can be 16.0 min/CV.

[0102] After loading, the column is washed with 3 column volumes of the 20 mM sodium acetate, pH 5.2-5.6 buffer. The column is then eluted using

